

SAFETY DATA SHEETS

EPOXY PRIMER PART A

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Epoxy Primer Part A
MANUFACTURER: Incredible Products LLC.
ADDRESS: 1221 Stewart Rd. Lima, OH 45801
INFORMATION PHONE: 567-297-3700
EMERGENCY PHONE: 800-424-9300
REVISION DATE: January 7, 2026

SECTION 2: HAZARDOUS IDENTIFICATION

Classification:

Skin Irritation - Category 2
Eye Irritation - Category 2A
Respiratory Sensitizer (Solid/Liquid) - N/A
Skin Sensitizer - Category 1
Carcinogenicity - Category 2

Signal Word:

Warning

Hazardous Statements - Health:

H319 - May cause eye irritation
H315 - May cause skin irritation
H317 - May cause an allergic skin reaction
H335 - May be harmful if inhaled

Precautionary Statements - General:

P101 - If medical advice is needed, have a product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention:

P210 - Keep away from heat/sparks/open flames/hot surfaces.
P264 - Wash thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P284 - <In case of inadequate ventilation> wear respiratory protection.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.

Precautionary Statements - Response:

P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.
P321 - Specific treatment (see section 4 on this SDS).
P362 + P364 - Take off contaminated clothing. And wash it before reuse.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage:

P405 - Store locked up.

Precautionary Statements - Disposal:

P501 - Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>UNIT</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
Bisphenol A Resin	25068-38-6		N/E	N/E
Glycidyl Ether	2461-15-6		N/E	N/E
Crystalline Silica	14808-60-7		0.1MG/M3	0.1MG/M3

SECTION 2 NOTES: *Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION 4: FIRST AID MEASURES

Inhalation:

If any breathing problems occur during use. LEAVE THE AREA and get fresh air. If problems remain or occur later IMMEDIATELY get medical attention.

Skin Contact:

Wash affected areas thoroughly with soap and water. Remove contaminated clothing and laundry before re-use.

Eye Contact:

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention. Avoid direct contact. Wear chemical protective gloves, if necessary.

Ingestion:

Induce vomiting only if large amounts of material are ingested, and otherwise do not induce vomiting. In either case, consult a physician.

SECTION 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Use extinguishing media appropriate for surrounding fire. The product itself does not burn.

Unsuitable Extinguishing Media:

N/A

Specific Hazards in Case of Fire:

Water contamination will produce carbon dioxide

Fire-fighting Procedures:

Isolate the immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from the immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions:

Wear NIOSH approved self-contained breathing apparatus in positive pressure mode with a full-face piece. Boots, gloves (neoprene), goggles, and full protective clothing are also required. Care should always be exercised in dust/mist areas.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedure:

Keep unnecessary people away; isolate hazard areas and deny entry. Do not touch or walk through spilled material. Clean up immediately. Scoop up or vacuum into a container for reclamation or disposal to avoid dusting.

Recommended Equipment:

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions:

Avoid breathing vapors. Avoid contact with skin, eyes or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

SECTION 7: HANDLING AND STORAGE

General:

Wash hands after use.
Do not get in eyes, on skin or on clothing.
Do not breathe vapors or mists.
Use good personal hygiene practices.
Eating, drinking and smoking in work areas is prohibited.
Remove contaminated clothing and protective equipment before entering eating areas.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits.
The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements:

Store in a cool dry place. Seal all partially used containers.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect workers, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. When airborne concentrations exceed or are expected to exceed the TLV, use MSHA/NIOSH approved positive pressure supplied air respirator with a full-face piece or an air supplied hood. For emergencies, use a positive pressure self-container breathing apparatus.
Air purifying (cartridge type) respirators are not approved for protection against isocyanates.

Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY: 1.35
BOILING POINT: 464F
EVAPORATION RATE: N/A
VAPOR DENSITY: HEAVIER THAN AIR
SOLUBILITY IN H₂O: SLIGHT

SECTION 10: STABILITY AND REACTIVITY

Stability:

This product is stable when properly stored at normal temperature and pressures.

Conditions to Avoid:

Contact with open flames and all sources of ignitions and sparks

Hazardous Reactions/Polymerization:

Will not occur under normal conditions.

Incompatible Materials:

Strong oxidants; Strong acids

Hazardous Decomposition Products:

Carbon oxides and traces of incomplete carbon compounds, silicon dioxide, metal oxides and formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

N/A

SECTION 12: ECOLOGICAL INFORMATION

N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal:

Waste management should be in full compliance with federal, state, and local laws.

SECTION 14: TRANSPORTATION INFORMATION

U.S. DOT Information: Not regulated

IMDG Information: Not regulated

IATA Information: Not regulated

SECTION 15: REGULATORY INFORMATION

N/A

SECTION 16: OTHER INFORMATION

DISCLAIMER

The information contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.