



TECHNICAL DATA SHEET

TRANSFORMER 3000# 3 X 3 MM DRY POLISH PAD

PRODUCT DESCRIPTION

The Concrete Protector's Transformer 3000#- 3 x 3 MM Dry Polish Pad is a high-grit, velcro-backed polishing tool used in the final stages of concrete floor polishing.

STANDARD COLORS: Red

OTHER COLORS ALSO AVAILABLE: N/A

REVISION DATE: February 13, 2026

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A

TACK FREE (DRY TO TOUCH): N/A

RECOAT OR TOPCOAT: N/A

LIGHT FOOT TRAFFIC: N/A

FULL CURE: N/A

COVERAGE

Recommended for the final polishing stage in concrete floor refinement

COVERAGE: 7,000-10,000 sq. ft. per set

MIX RATIO: N/A

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: Single piece

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A

COMPRESSIVE STRENGTH: N/A

TENSILE STRENGTH: N/A

ADHESION: N/AVISCOSITY: N/A

ABRASION RESISTANCE: N/A

ULTIMATE ELONGATION: N/A

HARDNESS: N/A

VOLATILE ORGANIC CONTENT: N/A

SHELF LIFE: N/A

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- 3000# grit is designed for finishing, not for grinding or leveling
- Must be used after progressive lower grit polishing
- Not suitable for wet polishing systems

BENEFITS

- Delivers a mirror-like finish and high reflectivity
- Designed for dry polishing, which simplifies cleanup and eliminates slurry management
- Velcro backing allows for quick tool changes



TECHNICAL DATA SHEET

TRANSFORMER 3000# 3 X 3 MM DRY POLISH PAD

INSTRUCTIONS

- 1) Ensure the surface has already been mechanically refined using lower-grit pads (typically 50#, 100#, 200#, 400#, 800#, and 1500#) to remove imperfections and open up the surface.
- 2) Mount the 3" Velcro-backed pad onto a planetary floor polisher, edge polisher, or hand tool with Velcro attachment.
- 3) Use a low-to medium-speed grinder/polisher with even downward pressure.
- 4) Run the machine over the surface in overlapping passes (typically 50% overlap), keeping the machine moving at a consistent pace to avoid overheating or pad glazing.
- 5) Polish in multiple directions (north-south, then east-west) for even clarity and gloss.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIALS AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM