



# TECHNICAL DATA SHEET

## 5" FLEXIBLE RUBBER BACKER PAD, 5/8" THREAD

### PRODUCT DESCRIPTION

The Concrete Protector's 5" Flexible Rubber Backer Pad is designed for connecting polishing tools and polishing pads to polishing and sanding machines.

**STANDARD COLORS:** Black  
**OTHER COLORS ALSO AVAILABLE:** N/A  
**REVISION DATE:** March 31, 2026

### CURE SCHEDULE (75°)

**POT LIFE:** N/A  
**TACK FREE (DRY TO TOUCH):** N/A  
**RECOAT OR TOPCOAT:** N/A  
**LIGHT FOOT TRAFFIC:** N/A  
**FULL CURE:** N/A

### COVERAGE

Recommended for sander/polishers equipped with a brass arbor with 5/8" thread

**COVERAGE:** N/A  
**MIX RATIO:** N/A

**RECOMMENDED FILM THICKNESS:** N/A

**PACKAGING INFORMATION:** 1 piece

### PHYSICAL PROPERTIES

**WEIGHT:** 5.8 oz.  
**SIZE:** 5 in.  
**MATERIAL:** Rubber  
**AXLE DIAMETER:** 5/8-11

### CHEMICAL RESISTANCE

N/A

### LIMITATIONS

N/A

### BENEFITS

- Super flexible
- Made with premium grade rubber, more suitable for polishing edges
- Use top quality nylon, will not peel off
- Fits all same size sander/polishers, Brass arbor with 5/8" 11 Thread

### INSTRUCTIONS

- 1) Place Backer Pad rounded side first onto the spindle of polisher or sander
- 2) Attach the barrel center nut and turn clockwise
- 3) Tighten nut with a spindle wrench
- 4) Use a variable-speed grinder: Lower speeds for polishing (especially resin pads), Medium speeds for sanding or light grinding
- 5) Avoid high RPMs that can damage pads or cause overheating
- 6) Turn the machine on before touching the surface
- 7) Keep the pad flat or slightly angled
- 8) Use smooth, overlapping passes



## TECHNICAL DATA SHEET

# 5" FLEXIBLE RUBBER BACKER PAD, 5/8" THREAD

### NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM

5" FLEXIBLE RUBBER BACKER PAD, 5/8" THREAD