



TECHNICAL DATA SHEET

AMERIPOLISH SURELOCK

PRODUCT DESCRIPTION

The Concrete Protector's Ameripolish® SureLock is a colorant for polished concrete

STANDARD COLORS: Various Colors

OTHER COLORS ALSO AVAILABLE: Black, Burnt Sienna, Caramel, Chestnut, Chocolate, Eggplant, Forest Green, Gold, Gray, Green, JCP Street, Mahogany, Maroon, Midnight Black, Patriot Blue, Pine Green, Raw Sienna, Red, Saddle Brown, Sand, Sepia, Slate Blue, Terra Cotta, Turquoise, Walnut

REVISION DATE: March 31, 2026

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A

TACK FREE (DRY TO TOUCH): N/A

RECOAT OR TOPCOAT: N/A

LIGHT FOOT TRAFFIC: N/A

FULL CURE: 7 days

COVERAGE

Recommended for diamond-polished concrete

COVERAGE PER GALLON: 400 sq. ft. per gal

MIX RATIO: 1 part Surelock to 1 part Color Solve OR 1 part Surelock to 1 part water

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 1 gal, 5 gal

PHYSICAL PROPERTIES

APPLICATION: Spray & microfiber mop

COMPRESSIVE STRENGTH: N/A

APPEARANCE: Various colors

ADHESION: N/A

VISCOSITY: N/A

ABRASION RESISTANCE: N/A

ULTIMATE ELONGATION: N/A

HARDNESS: N/A

VOLATILE ORGANIC CONTENT: Compliant (38 g/L)

SHELF LIFE: Indefinite

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- For indoor use only
- New concrete must cure for at least 28 days before application
- Ambient temperature during application should be 40-100°F (4-38°C).
- Keep product from freezing
- Do not mix with other chemicals

BENEFITS

- Consistent, rich penetrating color with UV stabilizers resist fading
- Liquid concentrate eliminates 3-hour wait to dissolve dye required by other products
- Mixes with water
- VOC compliant



TECHNICAL DATA SHEET

AMERIPOLISH SURELOCK

INSTRUCTIONS

- 1) Grind up to 200-grit resin bond diamonds. (If not using a 200-grit step, grind up to 100-grit resins.)
- 2) Remove all dust and debris. If wet cleaning is performed, allow surfaces to dry.
- 3) Vacuum surface thoroughly.
- 4) Spray Ameripolish® SureLock™ Concrete Dye to slightly wet surface without creating puddles. Apply in a consistent, overlapping circular motion, holding the wand approximately 12-18 inches above the surface.
- 5) Allow the surface to dry.
- 6) Remove dye residue with an auto scrubber fitted with a white pad and water. Perform white-rag test to assure that residue is removed.
- 7) Spray Ameripolish® 3D HS in an overlapping motion. Avoid puddles.
- 8) Allow the surface to dry.
- 9) Polish up to 400-grit resin bond diamonds.
- 10) Apply Ameripolish® SureLock™ Concrete Dye again for maximum color, using the same method as step 4.
- 11) Allow the surface to dry.
- 12) Remove dye residue with an auto scrubber fitted with a white pad and water.
- 13) Polish with 800-grit resins, and 1500-grit or 3000-grit if desired.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM