



TECHNICAL DATA SHEET

ELASTATHANE AR POLYMER

PRODUCT DESCRIPTION

The Concrete Protector's ElastaThane AR Polymer is a 100% solids, aromatic isocyanate, single component, moisture cure binder for rubber, SBR, EPDM granules and various rock aggregates.

STANDARD COLORS: Clear
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: March 7, 2022

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A
TACK FREE (DRY TO TOUCH): N/A
RECOAT OR TOPCOAT: N/A
LIGHT FOOT TRAFFIC: N/A
FULL CURE: N/A

COVERAGE

Recommended for use with rubber, SRB, and EPDM granules

COVERAGE PER GALLON: N/A

MIX RATIO: 1:1 with solvent for priming/ 1:4 with rubber granules (measured in pounds)

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 5 gal.

PHYSICAL PROPERTIES

SPECIFIC GRAVITY: 1.07
VISCOSITY: 3000 ± 500 cps
TOTAL SOLIDS BY WEIGHT, ASTM D-2369: 100%
TOTAL SOLIDS BY VOLUME, ASTM D-2697: 100%
TEAR RESISTANCE, DIE C- ASTM D-624: 160 ± 25 pli
28.0 ± 4.8 kN/m
TENSILE STRENGTH, ASTM D-412: 2000 ± 200 psi
13.8 ± 1.4 MPa
ULTIMATE ELONGATION, ASTM D-412: 475 ± 50%

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Not UV resistant
- Once the container has been opened, care should be taken to exclude moisture.
- The most favorable temperature for storage is 25-35°C. If stored at higher temperatures, or if moisture is not excluded, an undesirable increase in viscosity will occur.
- This product contains Isocyanates.

BENEFITS

- Solvent Free
- Long Pot Life
- Single Component
- Resilient
- Cold Temperature Flexibility
- Hydrolytic Stability
- Good Freeze-Thaw Flexibility
- Excellent Binding Characteristics
- MDI Based - Does Not Contain TDI

ELASTATHANE AR POLYMER



TECHNICAL DATA SHEET

ELASTATHANE AR POLYMER

INSTRUCTIONS

PRIMING

- 1) Combine 1 part ElastaThane AR Polymer and 1 part solvent, mix well
- 2) Apply to surface using a $\frac{3}{8}$ " nap roller

BINDING RUBBER

- 1) Combine 1 part ElastaThane AR Polymer and 4 parts rubber granules (measured by the pound), mix well
- 2) Apply to surface using a screed box and thickness gauge or metal trowel

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM