



TECHNICAL DATA SHEET

PERMAFLEX ACCELERATOR

PRODUCT DESCRIPTION

SaniTred's PermaFlex Accelerator is an additive added to PermaFlex and SuperThane to accelerate dry time.

STANDARD COLORS: Pale Yellow
OTHER COLORS ALSO AVAILABLE: N/A
FEBRUARY 15, 2023

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL VOLUME): N/A
TACK FREE (DRY TO TOUCH): N/A
RECOAT OR TOPCOAT: N/A
LIGHT FOOT TRAFFIC: N/A
FULL CURE: N/A

COVERAGE

Recommended as a drying accelerate for PermaFlex and SuperThane

COVERAGE: N/A

MIXED RATIO: 6.4 oz. per 1 gal. for slow set/
12.8 oz. per gal. for fast set)

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 6.4 oz. bottle, 1 quart bottle

PHYSICAL PROPERTIES

SPECIFIC GRAVITY: 0.867

PHYSICAL STATE: Liquid

ODOR: Amine like odor

SOLUBILITY: Reacts slowly

VISCOSITY: N/A

FLASH POINT: 93 °C (200 °F)

BOILING POINT: 200 °C (392 °F)

MELTING POINT: N/A

DECOMPOSITION TEMPERATURE: N/A

LEL: N/A

VAPOR PRESSURE: N/A

PH: N/A

VOC%: N/A

DENSITY LBS/GAL: N/A

POUNDS PER CUBIC FOOT: N/A

ODOR THRESHOLD: N/A

PARTITION COEFFICIENT WATER/N-OCTANOL: N/A

FLASH POINT METHOD: TCC

BOILING RAN: N/A

EVAPORATION RATE: N/A

AUTO-IGNITION TEMPERATURE: N/A

UEL: N/A

VAPOR DENSITY: Not Available

FLAMMABILITY: N/A

PERCENT VOLATILE: N/A

CHEMICAL RESISTANCE

N/A

PERMAFLEX ACCELERATOR



TECHNICAL DATA SHEET

PERMAFLEX ACCELERATOR

LIMITATIONS

- Additive for PermaFlex and SuperThane

BENEFITS

- Can be used for slow set or fast set
- Can be used for PermaFlex and SuperThane

INSTRUCTIONS

- 1) Combine correct measurements of PermaFlex or SuperThane and PermaFlex Accelerator (6.4 oz. per 1 gal. for slow set/ 12.8 oz. per gal. for fast set)
- 2) Mix until well blended

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM